

AIR Series Access Control Panel ICAIR-200



Reference image only*

IDCUBE's AIR is an enterprise-grade series of Access Control panels supporting advanced web-socket based real-time auto-push communication protocol. The panel support features such as anti-passback, first-card opening, multi-card opening, duress password entry, embedded card verification & auxiliary input/output linkages.

ICAIR-200 Seamlessly integrates with IDCUBE's "Access360" & "INEST" access control applications.

ICAIR-200 access control panel is a 2 door 4 reader control panel along with optional accessories, i.e., UL certified power supply, charging circuit, battery, and tamper switch. The control panel supports upto 6 inputs & 4 outputs

KEY FEATURES

Fully functional hardware/ firmware infrastructure for IDCUBE's Access360 & INEST applications

2 door 4 reader control panel with 6 inputs & 4 outputs.

30,000 card holders and 100,000 events capacity

Supports both TCP/IP and RS-485 communication

Web-socket based auto-push protocol facilitates seamless compatibility with IDCUBE's INEST cloud access control

Supports different Wiegand formats

Connects with a variety of electric locks, sensors, exit buttons, alarm devices & indicators

When not actively communicating with Acces360 application, the AIR functions offline performing all access decisions & event logging

Over-current & over-voltage protection for all input/output terminals

Can be integrated with 3rd party systems such as Intrusion Detection, Fire Alarm and Elevator Control system

*The panel image illustrates component assembly and may not represent the actual controller board

TECHNICAL SPECIFICATIONS

Characteristic	Parameter
Number of Doors Controlled	2 Door
Number of Readers Supported	4 readers on Wiegand/ RS-485
Types of Readers Supported	Wiegand, RS-485
Number of Inputs	6 (2 for Exit button, 2 for Door status, 2 for Aux)
Electronic lock Relay Outputs	2 (Relay rating: 2A @ 36VDC; Wet & Dry)
Auxiliary Relay Outputs	2 (Relay rating: 1.25A @ 36VDC; Dry only)
Card Holders Capacity	30,000
Log Events Capacity	100,000
Communication	TCP/IP & RS-485
Power Input	12VDC +/- 10%, 2A maximum
Dimensions (Board only)	6.3 in. × 4.17 in. (160mm × 106 mm)
CPU	32 bit 1.2GHz
RAM	128 MB
Flash Memory	256MB
Operating Temperature	0-45°C
Operating Humidity	20% to 80%
Certification	CE, FCC, ROHS
Part Code	ICAIR-200-EXXXXXX ¹

¹EXXXXXX refers to enclosure type along with accessories such as power supply, charging circuit, battery, and tamper switch; Please refer enclosure datasheet for details

For more information:
www.idcubesystems.com

IDCUBE Identification Systems Pvt. Ltd.
B-19, Sector-2, NOIDA 201301,
UTTAR PRADESH, INDIA
+91 120 4130715
contact@idcubesystems.com

